



BOSCH

Invented for life

FAA-500-SB-H Surface Mount Back Box with Damp Room Seal



This is used as an alternative to the Ceiling Mount Back Box. The Surface Mount Back Boxes are designed for flush-mounted cable feed and surface-mounted cable feed with cable protection conduits.

The FAA-500-SB-H has an additional seal for damp rooms.

Functions

The inputs for surface-mounted cable feed are pre-punched. For flush-mounted cable feed, two inlets are provided in the base:

- Each 20 mm (0.75 inch) for PG 13.5 threads
- Each 25 mm (1.0 inch) for 3/4" cable protection conduit

In the case of cable feed via PG 13.5 threads, cables with diameters of up to 1.2 cm can be used.

The base is fitted using screws at four attachment points.

Technical Specifications

Dimensions	Ø 150 mm x 82 mm
Housing material	Polycarbonate (PC-FR)
Housing color	White (RAL 9003)
Weight (without/with packaging)	Approx. 225 g/330 g

Ordering Information

FAA-500-SB-H Surface Mount Back Box with Damp Room Seal

FAA-500-SB-H

for special applications where it is not possible to flush-mount the 500 and 520 Series Fire Detectors in a ceiling

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6258 5511
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by